



STRIP LED 12W 24V IP20

5 metri



CODICE

PARAMETRI BASE

	Misure	Unità di Taglio	Input Volt	Watt nominali	Watt effettivi
AV2582CIAA	5000x8x1.5mm	8LED/50mm	24VDC	12W/m	11W/m
AV4495CIAA	5000x8x1.5mm	8LED/50mm	24VDC	12W/m	11W/m
AV2580NIAA	5000x8x1.5mm	8LED/50mm	24VDC	12W/m	11W/m
AV4421WIAA	5000x8x1.5mm	8LED/50mm	24VDC	12W/m	11W/m
AV2581WIAA	5000x8x1.5mm	8LED/50mm	24VDC	12W/m	11W/m
AV6270WIAA	5000x8x1.5mm	8LED/50mm	24VDC	12W/m	11W/m
AV4241CIAA	5000x8x1.5mm	8LED/50mm	24VDC	12W/m	11W/m
AV4240NIAA	5000x8x1.5mm	8LED/50mm	24VDC	12W/m	11W/m
AV4239WIAA	5000x8x1.5mm	8LED/50mm	24VDC	12W/m	11W/m

PARAMETRI FOTOMETRICI

CRI	Colore Luce	Lumen nominali	Lumen effettivi	Classe	IP
≥80	6000K	1800LM/m	1650LM/m	D	IP20
≥80	5000K	1800LM/m	1630LM/m	D	IP20
≥80	4000K	1800LM/m	1630LM/m	D	IP20
≥80	3500K	1800LM/m	1560LM/m	D	IP20
≥80	3000K	1800LM/m	1580LM/m	D	IP20
≥80	6000K (10000+K)	1800LM/m	1650LM/m	D	IP65
≥80	4000K (5500K)	1800LM/m	1630LM/m	D	IP65
≥80	3000K (3500K)	1800LM/m	1580LM/m	D	IP65

I dati sopra riportati sono il risultato del test di una striscia da 1m senza processo di protezione IP. Il processo di protezione IP porta modifiche alle dimensioni, colore luce K e flusso luminoso.

