



STRIP LED 26W 24V

5 metri



CODICE

PARAMETRI BASE

	Misure	Unità di Taglio	Input Volt	Watt nominali	Watt effettivi
AV2631CIAA	5000x10x1.5mm	8LED/50mm	24VDC	26W/m	23.5W/m
AV3069CIAA	5000x10x1.5mm	8LED/50mm	24VDC	26W/m	23.5W/m
AV2632NIAA	5000x10x1.5mm	8LED/50mm	24VDC	26W/m	23.5W/m
AV2633WIAA	5000x10x1.5mm	8LED/50mm	24VDC	26W/m	23.5W/m
AV2634WIAA	5000x10x1.5mm	8LED/50mm	24VDC	26W/m	23.5W/m
AV2845CIAA	5000x10x2.5mm	8LED/50mm	24VDC	26W/m	23.5W/m
AV2846NIAA	5000x10x2.5mm	8LED/50mm	24VDC	26W/m	23.5W/m
AV2847WIAA	5000x10x2.5mm	8LED/50mm	24VDC	26W/m	23.5W/m
AV2848WIAA	5000x10x2.5mm	8LED/50mm	24VDC	26W/m	23.5W/m

PARAMETRI FOTOMETRICI

CRI	Colore Luce	Lumen nominali	Lumen effettivi	Classe	IP
≥80	6000K	3600LM/m	3520LM/m	A+	IP20
≥80	5000K	3600LM/m	3450LM/m	A+	IP20
≥80	4000K	3600LM/m	3450LM/m	A+	IP20
≥80	3000K	3600LM/m	3350LM/m	A+	IP20
≥80	2500K	3600LM/m	3280LM/m	A+	IP20
≥80	6000K (10000K+)	3600LM/m	3520LM/m	A+	IP65
≥80	4000K (5500K)	3600LM/m	3450LM/m	A+	IP65
≥80	3000K (3500K)	3600LM/m	3350LM/m	A+	IP65
≥80	2500K	3600LM/m	3280LM/m	A+	IP65

I dati sopra riportati sono il risultato del test di una striscia da 1m senza processo di protezione IP. Il processo di protezione IP porta modifiche alle dimensioni, colore luce K e flusso luminoso.

