

DOWNLIGHT DA INCASSO LINEARE LED OSRAM



3 LED



6 LED



12 LED

220-240V



38°



≥80



<19



CODICE	PARAMETRI BASE			
	Misure	Incasso	Vtaggio	Watt effettivi
AV5073NSAB	68,5x30,5x35,6mm	64x26mm	220-240V	4W
AV5073WSAB	68,5x30,5x35,6mm	64x26mm	220-240V	4W
AV5078NSAB	125,5x30,5x35,6mm	121x26mm	220-240V	8W
AV5078WSAB	125,5x30,5x35,6mm	121x26mm	220-240V	8W
AV5080NSAB	239,5x30,5x35,6mm	235x26mm	220-240V	15W
AV5080WSAB	239,5x30,5x35,6mm	235x26mm	220-240V	15W

PARAMETRI FOTOMETRICI					
CRI	UGR	Colore Luce	Lumen	Classe Energetica	IP
≥80	<19	4200K	287LM	G	IP25
≥80	<19	2700K	287LM	G	IP25
≥80	<19	4200K	575LM	G	IP25
≥80	<19	2700K	575LM	G	IP25
≥80	<19	4200K	1078LM	G	IP25
≥80	<19	2700K	1078LM	G	IP25

