


DOWNLIGHT DA INCASSO QUADRATO LED OSRAM



1 LED

4 LED

9 LED

16 LED

25 LED

CODICE	PARAMETRI BASE				PARAMETRI FOTOMETRICI					
	Misure	Incasso	Voltaggio	Watt effettivi	CRI	UGR	Colore Luce	Lumen	Classe Energetica	IP
AV5072NSAB	30,5x30,5x35,6mm	26x26mm	220-240V	2W	≥80	<19	4200K	153LM	G	IP25
AV5072WSAB	30,5x30,5x35,6mm	26x26mm	220-240V	2W	≥80	<19	3000K	153LM	G	IP25
AV5074NSAB	49,5x49,5x35,6mm	45x45mm	220-240V	5W	≥80	<19	4200K	382LM	G	IP25
AV5074WSAB	49,5x49,5x35,6mm	45x45mm	220-240V	5W	≥80	<19	3000K	382LM	G	IP25
AV5079NSAB	68x68x35,6mm	59x59mm	220-240V	10W	≥80	<19	4200K	765LM	G	IP25
AV5079WSAB	68x68x35,6mm	59x59mm	220-240V	10W	≥80	<19	3000K	765LM	G	IP25
AV5081NSAB	87,5x87,5x35,6mm	83x83mm	220-240V	15W	≥80	<19	4200K	1147LM	G	IP25
AV5081WSAB	87,5x87,5x35,6mm	83x83mm	220-240V	15W	≥80	<19	3000K	1147LM	G	IP25
AV5082NSAB	109,9x105,9x35,6mm	101,5x101,5mm	220-240V	20W	≥80	<19	4200K	1530LM	G	IP25
AV5082WSAB	109,9x105,9x35,6mm	101,5x101,5mm	220-240V	20W	≥80	<19	3000K	1530LM	G	IP25

