

APPLIQUE CILINDRO ORIENTABILE

Varie potenze e finiture



7W
15W
30W

WATT

220-240V



24°



CODICE	MISURE	ORIENTABILE	INPUT VOLT	WATT NOMINALI	OTTICA	COLORE LUCE	MATERIALE	LUMEN	ERP ECODESIGN	IP
AV6253CSAA	Ø72x97mm	Si	220-240V	7W	24°	5000K	All. Bianco	595Lm	F	IP20
AV6253NSAA	Ø72x97mm	Si	220-240V	7W	24°	4000K	All. Bianco	595Lm	F	IP20
AV6253WSAA	Ø72x97mm	Si	220-240V	7W	24°	2700K	All. Bianco	595Lm	F	IP20
AV6511CSAA	Ø72x97mm	Si	220-240V	7W	24°	5000K	All. Nero	595Lm	F	IP20
AV6511NSAA	Ø72x97mm	Si	220-240V	7W	24°	4000K	All. Nero	595Lm	F	IP20
AV6511WSAA	Ø72x97mm	Si	220-240V	7W	24°	2700K	All. Nero	595Lm	F	IP20
AV6254CSAA	Ø90x110mm	Si	220-240V	15W	24°	5000K	All. Bianco	1200Lm	F	IP20
AV6254NSAA	Ø90x110mm	Si	220-240V	15W	24°	4000K	All. Bianco	1200Lm	F	IP20
AV6254WSAA	Ø90x110mm	Si	220-240V	15W	24°	2700K	All. Bianco	1200Lm	F	IP20
AV6516CSAA	Ø90x110mm	Si	220-240V	15W	24°	5000K	All. Nero	1200Lm	F	IP20
AV6516NSAA	Ø90x110mm	Si	220-240V	15W	24°	4000K	All. Nero	1200Lm	F	IP20
AV6516WSAA	Ø90x110mm	Si	220-240V	15W	24°	2700K	All. Nero	1200Lm	F	IP20
AV6295CSAA	Ø110x115mm	Si	220-240V	30W	24°	5000K	All. Bianco	2200Lm	F	IP20
AV6295NSAA	Ø110x115mm	Si	220-240V	30W	24°	4000K	All. Bianco	2200Lm	F	IP20
AV6295WSAA	Ø110x115mm	Si	220-240V	30W	24°	2700K	All. Bianco	2200Lm	F	IP20
AV6517NSAA	Ø110x115mm	Si	220-240V	30W	24°	4000K	All. Nero	2200Lm	F	IP20
AV6517WSAA	Ø110x115mm	Si	220-240V	30W	24°	2700K	All. Nero	2200Lm	F	IP20

