


FARETTO DOWNLIGHT BINARIO 48V



6W

10W

20W




43.5

112x22.5



43.5

220x22.5




43.5

435x22.5


CODICE	PARAMETRI BASE				PARAMETRI FOTOMETRICI					
	Misure	Watt	Input Volt	Tipo LED	CRI	UGR	Colore Luce	Lumen nominali	Rotazione	IP
AV6608WIAA	43,5x22,5x112 mm	6x1W	48VDC	COB DIMMERABILE	≥90	<12	3000K	531LM	-	IP20
AV6016NIAA	43,5x22,5x112 mm	6x1W	48VDC	COB	≥90	<12	4000K	531LM	-	IP20
AV6017WIAA	43,5x22,5x220 mm	10x1W	48VDC	COB	≥90	<12	3000K	905LM	-	IP20
AV6018NIAA	43,5x22,5x220 mm	10x1W	48VDC	COB	≥90	<12	4000K	905LM	-	IP20
AV6019WIAA	43,5x22,5x435 mm	20x1W	48VDC	COB	≥90	<12	3000K	1805LM	-	IP20
AV6020NIAA	43,5x22,5x435 mm	20x1W	48VDC	COB	≥90	<12	4000K	1805LM	-	IP20

FOTOMETRIE:




FARETTO 6W - 24°

H(m)	E(lx)	D(cm)
1	1619	45
2	405	91
3	180	136
4	101	182
5	65	227



FARETTO 10W - 24°

H(m)	E(lx)	D(cm)
1	3599	47
2	900	94
3	400	141
4	225	188
5	144	234



FARETTO 20W - 24°

H(m)	E(lx)	D(cm)
1	5761	46
2	1440	92
3	640	137
4	360	183
5	230	229

ACCESSORI:



Binario da incasso: AV6001XIAA



Binario superficie: AV6000XIAA

IMMAGINI:

