


# PANNELLO LED 60x60 40W UGR17 Dimmerabile



CODICE	MISURE	INPUT VOLT	WATT NOMINALI	DRIVER	CRI	COLORE LUCE	LUMEN NOMINALI	ERP ECODESIGN	IP
AV6780CSAA	595x595x24mm	220-240Vac	40W	Dimm. 0-10V	≥80	6000K	4000LM	E	IP20
AV6780NSAA	595x595x24mm	220-240Vac	40W	Dimm. 0-10V	≥80	4000K	4000LM	E	IP20
AV6780WSAA	595x595x24mm	220-240Vac	40W	Dimm. 0-10V	≥80	3000K	4000LM	E	IP20
AV6782CSAA	595x595x24mm	220-240Vac	40W	Dimm. Triac	≥80	6000K	4000LM	E	IP20
AV6782NSAA	595x595x24mm	220-240Vac	40W	Dimm. Triac	≥80	4000K	4000LM	E	IP20
AV6782WSAA	595x595x24mm	220-240Vac	40W	Dimm. Triac	≥80	3000K	4000LM	E	IP20
AV6781CSAA	595x595x24mm	220-240Vac	40W	Dimm. Dali	≥80	6000K	4000LM	E	IP20
AV6781NSAA	595x595x24mm	220-240Vac	40W	Dimm. Dali	≥80	4000K	4000LM	E	IP20
AV6781WSAA	595x595x24mm	220-240Vac	40W	Dimm. Dali	≥80	3000K	4000LM	E	IP20

DIMENSIONI

