

PROIETTORE PRO IP65 IK08 VARIE OTTICHE

LED Samsung/Lumileds - Driver SOSEN

IP65

GARANZIA
5 ANNI

LUMILEDS

50W
100W
200W

WATT

220-240V

Varie
a scelta160
Lm/WLUMILEDS
SAMSUNGCRI
>80

IK08



CODICE	PARAMETRI BASE					PARAMETRI FOTOMETRICI							
	Misure	Watt	Input Volt	Marchio LED	Finitura	CRI	Colore Luce CCT Selezionabile		Lumen nominali	Ottica	Classe Erp EcoDesign	IP	
AV6902-60XSAA	305x208x55mm	50W	220-240V	SAMSUNG	Nero	■	>80	3000K-4000K-6500K		8000LM	60°	D	IP65
AV6902-90XSAA	305x208x55mm	50W	220-240V	SAMSUNG	Nero	■	>80	3000K-4000K-6500K		8000LM	90°	D	IP65
AV6902-120XSAA	305x208x55mm	50W	220-240V	SAMSUNG	Nero	■	>80	3000K-4000K-6500K		8000LM	120°	D	IP65
AV6903-60XSAA	388x288x66mm	100W	220-240V	SAMSUNG	Nero	■	>80	3000K-4000K-6500K		16000LM	60°	D	IP65
AV6903-90XSAA	388x288x66mm	100W	220-240V	SAMSUNG	Nero	■	>80	3000K-4000K-6500K		16000LM	90°	D	IP65
AV6903-120XSAA	388x288x66mm	100W	220-240V	SAMSUNG	Nero	■	>80	3000K-4000K-6500K		16000LM	120°	D	IP65
AV6904-60XSAA	498x373x66mm	200W	220-240V	SAMSUNG	Nero	■	>80	3000K-4000K-6500K		32000LM	60°	D	IP65
AV6904-90XSAA	498x373x66mm	200W	220-240V	SAMSUNG	Nero	■	>80	3000K-4000K-6500K		32000LM	90°	D	IP65
AV6904-120XSAA	498x373x66mm	200W	220-240V	SAMSUNG	Nero	■	>80	3000K-4000K-6500K		32000LM	120°	D	IP65

