

# PANNELLO LED 60X60 40W alta luminosità

## Driver dimmerabile 0-10V

IP40

0-10V

GARANZIA  
3 ANNI

CE

RoHS  
COMPLIANT

40W

WATT

220-240V



5200Lm

LUMEN

CRI  
>80

CRI

120°

OTTICA

| CODICE     | PARAMETRI BASE |            |      |        | INFO |             |    |        |                   |      |
|------------|----------------|------------|------|--------|------|-------------|----|--------|-------------------|------|
|            | Misure         | Input Volt | Watt | Lumen  | CRI  | Colore Luce | IK | Driver | IP                |      |
| AV6913CSAA | 595x595x30mm   | 220-240V   | 40W  | 5200LM | ≥80  | 6000K       |    | IK05   | LIFUD dimm. 0-10V | IP40 |
| AV6913NSAA | 595x595x30mm   | 220-240V   | 40W  | 5200LM | ≥80  | 4000K       |    | IK05   | LIFUD dimm. 0-10V | IP40 |
| AV6913WSAA | 595x595x30mm   | 220-240V   | 40W  | 5200LM | ≥80  | 3000K       |    | IK05   | LIFUD dimm. 0-10V | IP40 |

\*\*Disponibile anche in versione dimmerabile TRIAC e DALI

### DIMENSIONI

