

PROIETTORE PRO IP66 IK08 VARIE OTTICHE

Driver LIFUD dimm. 1-10V

IP66

200W **WATT**

220-240V

Varie a scelta **OTTICA** 160 Lm/W **LUMEN** SMD 5050 **LED** CRI>70 **CRI**

IK08

CODICE	PARAMETRI BASE					PARAMETRI FOTOMETRICI						
	Misure	Watt	Input Volt	Marchio LED	Finitura	CRI	Colore Luce		Lumen nominali	Ottica	Classe Erp EcoDesign	IP
AV6910WSAA	190x351x115mm	200W	220-240V	LUMILEDS	Nero	■ >70	3000K	■	30000LM	90°	C	IP66
AV6910NSAA	190x351x115mm	200W	220-240V	LUMILEDS	Nero	■ >70	4000K	■	30000LM	90°	C	IP66
AV6910CSAA	190x351x115mm	200W	220-240V	LUMILEDS	Nero	■ >70	5000K	■	30000LM	90°	C	IP66
AV6910CSAA	190x351x115mm	200W	220-240V	LUMILEDS	Nero	■ >70	5700K	■	30000LM	60°	C	IP66
AV6989NSAA	190x351x115mm	200W	220-240V	LUMILEDS	Nero	■ >70	4000K	■	30000LM	Asimmetria 50°	C	IP66

**Altre ottiche disponibili 30°, 60°, 90° e asimmetrica polarizzata 50°

