

# FARETTO SPOT 48V DIMMERABILE PWM

In alluminio nero e bianco

TRACK LIGHT 48VDC



| CODICE     | MISURE    | INPUT VOLT | WATT NOMINALI | FINITURA         | CRI | COLORE LUCE | LUMEN NOMINALI | OTTICA     | IP   |
|------------|-----------|------------|---------------|------------------|-----|-------------|----------------|------------|------|
| AV6601NIAA | Ø35x55mm  | 48Vdc      | 4W            | Alluminio nero   | ≥90 | 4000K       | 378LM          | 36°        | IP20 |
| AV6600WIAA | Ø35x55mm  | 48Vdc      | 4W            | Alluminio nero   | ≥90 | 3000K       | 378LM          | 36°        | IP20 |
| AV7419NIAA | Ø35x55mm  | 48Vdc      | 4W            | Alluminio bianco | ≥90 | 4000K       | 378LM          | 36°        | IP20 |
| AV6641WIAA | Ø35x55mm  | 48Vdc      | 4W            | Alluminio bianco | ≥90 | 3000K       | 378LM          | 36°        | IP20 |
| AV6603NIAA | Ø45x70mm  | 48Vdc      | 7W            | Alluminio nero   | ≥90 | 4000K       | 554LM          | 36°        | IP20 |
| AV6602WIAA | Ø45x70mm  | 48Vdc      | 7W            | Alluminio nero   | ≥90 | 3000K       | 554LM          | 36°        | IP20 |
| AV7020NIAA | Ø45x70mm  | 48Vdc      | 7W            | Alluminio bianco | ≥90 | 4000K       | 554LM          | 36°        | IP20 |
| AV6642WIAA | Ø45x70mm  | 48Vdc      | 7W            | Alluminio bianco | ≥90 | 3000K       | 554LM          | 36°        | IP20 |
| AV6605NIAA | Ø55x86mm  | 48Vdc      | 12W           | Alluminio nero   | ≥90 | 4000K       | 823LM          | 36°        | IP20 |
| AV6604WIAA | Ø55x86mm  | 48Vdc      | 12W           | Alluminio nero   | ≥90 | 3000K       | 823LM          | 36°        | IP20 |
| AV7421NIAA | Ø55x86mm  | 48Vdc      | 12W           | Alluminio bianco | ≥90 | 4000K       | 823LM          | 36°        | IP20 |
| AV6643WIAA | Ø55x86mm  | 48Vdc      | 12W           | Alluminio bianco | ≥90 | 3000K       | 823LM          | 36°        | IP20 |
| AV7569NIAA | Ø55x150mm | 48Vdc      | 20W           | Alluminio nero   | ≥90 | 4000K       | 1371LM         | 36°        | IP20 |
| AV7568WIAA | Ø55x150mm | 48Vdc      | 20W           | Alluminio nero   | ≥90 | 3000K       | 1371LM         | 36°        | IP20 |
| AV7571NIAA | Ø55x150mm | 48Vdc      | 20W           | Alluminio bianco | ≥90 | 4000K       | 1371LM         | 36°        | IP20 |
| AV7570WIAA | Ø55x150mm | 48Vdc      | 20W           | Alluminio bianco | ≥90 | 3000K       | 1371LM         | 36°        | IP20 |
| AV8220WIAA | Ø60x185mm | 48Vdc      | 20W           | Alluminio nero   | ≥90 | 3000K       | -              | Sagomatore | IP20 |
| AV8221WIAA | Ø60x185mm | 48Vdc      | 20W           | Alluminio bianco | ≥90 | 3000K       | -              | Sagomatore | IP20 |

