

## FARETTO BINARIO TRIFASE OTTICA ZOOM

Potenza e ottica regolabile



CODICE	MISURE	INPUT VOLT	WATT NOMINALI	FINITURA	CRI	COLORE LUCE SELEZIONABILE	LUMEN NOMINALI	OTTICA	IP
AV8454NIAA	Ø65x147mm	220-240Vac	10W-20W	All. Nero	≥90	4000K-3500K-3000K	1750LM-2050LM	24°>60°	IP20
AV8452BIAA	Ø65x147mm	220-240Vac	10W-20W	All. Bianco	≥90	4000K-3500K-3000K	1750LM-2050LM	24°>60°	IP20
AV8455NIAA	Ø80x171mm	220-240Vac	20W-35W	All. Nero	≥90	4000K-3500K-3000K	3100LM-3850LM	24°>60°	IP20
AV8453BIAA	Ø80x171mm	220-240Vac	20W-35W	All. Bianco	≥90	4000K-3500K-3000K	3100LM-3850LM	24°>60°	IP20

## FARETTO BINARIO TRIFASE 12W

Varie finiture disponibili



CODICE	MISURE	INPUT VOLT	WATT NOMINALI	FINITURA	CRI	COLORE LUCE	LUMEN NOMINALI	OTTICA	IP
AV8404NIAA	Ø55x120mm	220-240Vac	12W	Alluminio nero	≥90	4000K	937LM	36°	IP20
AV8403WIAA	Ø55x120mm	220-240Vac	12W	Alluminio nero	≥90	3000K	937LM	36°	IP20
AV8405WIAA	Ø55x120mm	220-240Vac	12W	Alluminio nero	≥90	2700K	937LM	36°	IP20
AV8402NIAA	Ø55x120mm	220-240Vac	12W	Alluminio bianco	≥90	4000K	937LM	36°	IP20
AV8401WIAA	Ø55x120mm	220-240Vac	12W	Alluminio bianco	≥90	3000K	937LM	36°	IP20
AV8406WIAA	Ø55x120mm	220-240Vac	12W	Alluminio bianco	≥90	2700K	937LM	36°	IP20
AV8407WIAA	Ø55x120mm	220-240Vac	12W	Alluminio acciaio	≥90	3000K	937LM	36°	IP20
AV8408WIAA	Ø55x120mm	220-240Vac	12W	Alluminio oro	≥90	3000K	937LM	36°	IP20
AV8409WIAA	Ø55x120mm	220-240Vac	12W	Alluminio argento	≥90	3000K	937LM	36°	IP20